

## N-Type HJT Module

# 700-720W


Max. Power Output

# 0~+3%

Power Tolerance

# 23.18%

Module Efficiency



HJT Half-cut Bifacial Dual-Glass Module(MBB)  
Module type: SKA611HDGDC

### Product advantages



#### N-type HJT technology for lower LCOE

The lower temperature coefficient and better low irradiance performance of HJT technology can effectively reduce LCOE.




#### Fire class A, harsh environment adaptability

The module adopt a double glass structure, which can adapt to all kinds of harsh environment, and the fire rating can reach Class A.



#### 30-year power warranty

The average life of dual-glass module is 30 years, 5 years longer than that of single-glass modules.




#### Double-sided power generation, higher income

The dual-glass module has a bifaciality of up to 90% and a power generation gain of 7%-30% on the back side.

### LINEAR PERFORMANCE WARRANTY

**15** Years product warranty on materials and workmanship

**30** Years linear power output warranty



30 years decay  $\leq$  **0.25%** annually on average

### CERTIFICATES



IEC 61215 / IEC 61730

## ELECTRICAL PARAMETERS @ STC

	700	705	710	715	720
Max. Power Output Pmax (W)	700	705	710	715	720
Power Tolerance	0~+3%	0~+3%	0~+3%	0~+3%	0~+3%
Max. Power Voltage Vmp (V)	41.52	41.55	41.59	41.64	41.69
Max. Power Current Imp (A)	16.86	16.97	17.07	17.17	17.27
Open Circuit Voltage Voc (V)	49.31	49.35	49.40	49.45	49.51
Short Circuit Current Isc (A)	17.72	17.83	17.94	18.04	18.14
Module Efficiency(%)	22.53	22.70	22.86	23.02	23.18

\*STC (Standard Test Condition): Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass 1.5

\*Measurement Tolerance (±3.0%)

## Integrated Power @ STC (Reference to 710W front)

	746	781	815	850	886
Max. Power Output Pmax (W)	746	781	815	850	886
Max. Power Voltage Vmp (V)	43.46	43.46	43.36	43.36	43.36
Max. Power Current Imp (A)	17.16	17.97	18.79	19.61	20.43
Open Circuit Voltage Voc (V)	50.71	50.71	50.81	50.81	50.81
Short Circuit Current Isc (A)	18.11	18.98	19.84	20.70	21.56
Power Gains	5%	10%	15%	20%	25%


## MECHANICAL PARAMETERS

Cell Type	HJT 210x105mm
Number of Cells	132pcs(6x22)
Dimensions(L*W*H)	2384x1303x33mm
Weight	38.3kg
Frame	Anodised Aluminum
Junction Box	IP68, 3 bypass diodes
Cable,Length	4.0mm <sup>2</sup> , 300mm


## TEMPERATURE COEFFICIENTS

Temperature Coefficients of Pmp	-0.24%/°C
Temperature Coefficients of Voc	-0.22%/°C
Temperature Coefficients of Isc	+0.047%/°C

## I-V CURVES



## ASSEMBLY DRAWING (Unit:mm)



## OPERATING CONDITION

Maximum System Voltage(V)	1500(DC)
Operating Temperature(°C)	-40~+85
Max.Wind Load /Snow Load(Pa)	2400/5400
Max.Series Fuse Rating(A)	35
Fire Rating	Class A
Bifaciality	90±5%
NOCT	45°C

## PACKAGE INFORMATION

Container 40'HQ	594pcs
Quantity / Pallet	33pcs
Size: 1310×1100×2520mm; Net weight: 1263.9kg; Gross weight: 1307.4kg	

